

## SAFETY DATA SHEET NO.21 TAR AND ADHESIVE REMOVER

SECTION 1: Identification of	of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	NO.21 TAR AND ADHESIVE REMOVER
Product number	21005, 21025, 21001CN, 21005CN, 21500CN
Internal identification	NO21/PB25/210114
1.2. Relevant identified use	es of the substance or mixture and uses advised against
Identified uses	Solvent based cleaner for tar and adhesives
1.3. Details of the supplier	of the safety data sheet
Supplier	Autoglym Works Road Letchworth Herts SG6 1LU UK sds@autoglym.com
1.4. Emergency telephone	number
Emergency telephone	+44 (0) 1462 489498 (24Hrs)
SECTION 2: Hazards ident	ification
2.1. Classification of the su	bstance or mixture
Classification (EC 1272/200	08)
Physical hazards	Flam. Liq. 3 - H226
Health hazards	Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304
Environmental hazards	Not Classified
2.2. Label elements Pictogram	
Signal word	Danger
Hazard statements	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements	<ul> <li>P102 Keep out of reach of children.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P261 Avoid breathing vapour/ spray.</li> <li>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</li> <li>P331 Do NOT induce vomiting.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P302+P352 IF ON SKIN: Wash with plenty of water.</li> </ul>
Contains	Naptha (Petroleum), Hydrotreated Heavy
Detergent labelling	≥ 30% aliphatic hydrocarbons, 5 - < 15% aromatic hydrocarbons, perfumes
Supplementary precautionary statements	P501 Dispose of contents/ container in accordance with national regulations.

### 2.3. Other hazards

SECTION 3: Composition/information on ingredients
---

3.2.	Mixtures

eavy	60-100%
EC number: 265-150-3	REACH registration number: 01- 2119486659-16-XXXX
	on <b>(67/548/EEC or 1999/45/EC)</b> 2;R45 Muta. Cat. 2;R46 Xn;R65
	10-309
EC number: 215-535-7	REACH registration number: 01- 2119488216-32-XXXX
Classificatio R10 Xn;R20	on <b>(67/548/EEC or 1999/45/EC)</b> 0/21 Xi;R38
	5-109
EC number: 225-878-4	REACH registration number: 01- 2119475527-28-XXXX
<b>Classificatio</b> Xi;R36/38	on (67/548/EEC or 1999/45/EC)
	EC number: 265-150-3 Classificatio Carc. Cat. 2 EC number: 215-535-7 Classificatio R10 Xn;R20 EC number: 225-878-4

## $\underline{\textbf{4.1. Description of first aid measures}}$

Inhalation

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Ingestion	Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.
Skin contact	Wash skin thoroughly with soap and water or use an approved skin cleanser.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention.
4.2. Most important symptoms	and effects, both acute and delayed
Inhalation	The product contains organic solvents. Vapours may cause drowsiness and dizziness. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.
Ingestion	Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. May cause discomfort. Nausea, vomiting. Diarrhoea.
Skin contact	May cause skin irritation.
Eye contact	Irritation of eyes and mucous membranes.
4.3. Indication of any immedia	te medical attention and special treatment needed
Specific treatments	Treat symptomatically.
SECTION 5: Firefighting meas	ures
5.1. Extinguishing media	
Suitable extinguishing media	Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from	om the substance or mixture
Specific hazards	Flammable liquid and vapour. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO2). Carbon monoxide (CO).
5.3. Advice for firefighters	
Protective actions during firefighting	Do not use water jet as an extinguisher, as this will spread the fire. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
SECTION 6: Accidental release	e measures
6.1. Personal precautions, pro	tective equipment and emergency procedures
Personal precautions	Avoid contact with skin, eyes and clothing. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours.
6.2. Environmental precaution	<u>S</u>
Environmental precautions	Do not allow to enter drainage system, surface or ground water. Prevent material from reaching sewage system, holes and cellars.
6.3. Methods and material for	containment and cleaning up
Methods for cleaning up	Absorb small quantities with paper towels and evaporate in a safe place. Absorb spillage with non-combustible, absorbent material. No smoking, sparks, flames or other sources of ignition near spillage.

Relative density

Solubility(ies)

~ 0.8

Insoluble in water.

## NO.21 TAR AND ADHESIVE REMOVER

## 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

SECTION 7: Handling and sto	rage	
7.1. Precautions for safe handling		
Usage precautions	For personal protection, see Section 8.	
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Provide eyewash station. Wash hands thoroughly after handling.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage precautions	Store at room temperature. Store in accordance with local regulations.	
7.3. Specific end use(s)		
SECTION 8: Exposure Contro	ls/personal protection	
8.1. Control parameters		
Occupational exposure limits		
Xylene		
Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Sk		
WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.		
8.2. Exposure controls		
Protective equipment		
Appropriate engineering controls	Avoid inhalation of vapours.	
Eye/face protection	Wear eye protection.	
Hand protection	Wear protective gloves. The breakthrough time for any glove material may be different for different glove manufacturers.	
Hygiene measures	Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.	
SECTION 9: Physical and Chemical Properties		
9.1. Information on basic phys	ical and chemical properties	
Appearance	Liquid.	
Colour	Blue-green.	
Odour	Organic solvents.	
рН	Not applicable.	
Initial boiling point and range	150°C @	
Flash point	~ 36.9°C Setaflash closed cup.	
Deletive densit		

Viscosity	0.831 m²/s @ 40°C	
9.2. Other information		
SECTION 10: Stability and rea	activity	
10.1. Reactivity		
Reactivity	There are no known reactivity hazards associated with this product.	
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recommended.	
10.3. Possibility of hazardous reactions		
Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition.	
10.5. Incompatible materials		
Materials to avoid	Avoid contact with the following materials: Strong acids. Strong oxidising agents.	
10.6. Hazardous decomposition	on products	
Hazardous decomposition products	None at ambient temperatures.	
SECTION 11: Toxicological int	formation	
11.1. Information on toxicologi	cal effects	
Acute toxicity - dermal		
ATE dermal (mg/kg)	6,962.03	
Acute toxicity - inhalation		
ATE inhalation (gases ppm)	28,481.01	
ATE inhalation (vapours mg/l)	69.62	
ATE inhalation (dusts/mists mg/l)	9.49	
Aspiration hazard Aspiration hazard	May be harmful if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.	
SECTION 12: Ecological Infor	mation	
12.1. Toxicity		
Toxicity	Not determined.	
12.2. Persistence and degrada	ability	
Phototransformation	Not determined.	
Stability (hydrolysis)	Not determined.	
Biodegradation	Expected to be readily biodegradable.	
Biological oxygen demand	Not determined.	
12.3. Bioaccumulative potentia		

12.4. Mobility in soil	
12.5. Results of PBT and vPvB	3 assessment
12.6. Other adverse effects	
SECTION 13: Disposal conside	
13.1. Waste treatment method: General information	_
	Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
SECTION 14: Transport inform	nation
14.1. UN number	
UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993
14.2. UN proper shipping name	9
Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S. (White Spirit)
Proper shipping name (IMDG)	FLAMMABLE LIQUID, N.O.S. (White Spirit)
Proper shipping name (ICAO)	FLAMMABLE LIQUID, N.O.S. (White Spirit)
Proper shipping name (ADN)	FLAMMABLE LIQUID, N.O.S. (White Spirit)
14.3. Transport hazard class(e	<u>s)</u>
ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3
Transport labels	
14.4. Packing group ADR/RID packing group	111

ADR/RID packing group	
IMDG packing group	III
ADN packing group	III
ICAO packing group	III
14.5. Environmental hazards	

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user	
EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code	
Transport in bulk according to	Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

**SECTION 15: Regulatory information** 

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16
	December 2008 on classification, labelling and packaging of substances and mixtures (as
	amended).

### 15.2. Chemical safety assessment

SECTION 16: Other information	
Revision date	23/04/2015
Revision	15
SDS number	20915
Hazard statements in full	<ul> <li>H226 Flammable liquid and vapour.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H312 Harmful in contact with skin.</li> <li>H315 Causes skin irritation.</li> <li>H319 Causes serious eye irritation.</li> <li>H332 Harmful if inhaled.</li> <li>H336 May cause drowsiness or dizziness.</li> </ul>
Signature	Daniel Higgs

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.